bekin • Your Essential Connection

BELKIN SECURE FLIP 2-PORT KVM WITH AUDIO & REMOTE CONTROLLER

Security. Convenience. Control.



The Belkin Secure Flip 2-Port KVM Switch is the first secure KVM in the industry specifically designed for 2-isolated network environments.

Many Federal/Secure Desktop users are required to switch between two isolated networks and call for a KVM solution that is both secure and cost-effective.

Belkin's Flip KVM Switch addresses these needs with its small form factor and secure switching.

The Flip KVM switch enables users to securely switch between two sources while presenting information from each source at a time.

The Flip KVM switch securely toggles control of video, keyboard, mouse and audio between the two sources allowing navigation by selecting the switch push buttons or controlling it remotely via remote control device. The product supports all operating systems: Linux, Mac OS and Windows.

User's Desktop

Connections

DN-D Video
PRO
Audio
USB Keyboard Mouse

12V, 1A Power

Nouse

Report 2
Cable
PC 1

PC 2

PC 2

F1DN102F-3
Belkin Advanced Secure 2-Port Flip KVM

Belkin's Flip KVM targets any organization with Secure Desktops, such as government agencies, defense, intelligence and finance.

Key Features and Benefits

Designed for Secure Desktops in 2-network environments

Cost-effective, small footprint

- Real-time switching
 Offering an uninterrupted user experience
- Remote Control
 RC unit for easy placement & control
- Integrated cables
 Arrive with product, easy to install
- Hardware-based peripherals' isolation
 No dependency on firmware; no keyboard buffering or memory
- Unidirectional Optical Data Diodes
 Assuring data can flow from devices to host only
- Display plug & play (DDC) protection
 Leakage prevention through patented emulated technology; DDC/EDID fully functional
- Active anti-tampering system
 Always-on with 10 years battery; holographic tampering evident labels

NIAP CERTIFIED TO COMMON CRITERIA PROTECTION PROFILE PSS VER 3.0

This Belkin product is certified by NIAP to the latest Common Criteria Protection Profile PSS Ver 3.0, which exceeds EAL4 and PP PSS Ver. 2.1.

belkin...

Security. Convenience. Control.

F1DN102F-3 F1DN102N-3 F1DN102V-3

Belkin Secure Flip 2-Port KVM Switch Specification

No. of Computers 2 CONSOLE PORTS (DEVICES) Console Mouse and Keyboard Ports USB Type A Console Audio Jack 1/8" (3.5mm) female Console Video Port DVI-D VGA Console Remote Control Port 1/10" (2.5mm) female	HDMI 3840x2160 pixels (UHD 4K)
Console Mouse and Keyboard Ports USB Type A Console Audio Jack 1/8" (3.5mm) female Console Video Port DVI-D VGA	
Console Audio Jack 1/8" (3.5mm) female Console Video Port DVI-D VGA	
Console Video Port DVI-D VGA	
Console Remote Control Port 1/10" (2.5mm) female	3840x2160 pixels (UHD 4K)
	3840x2160 pixels (UHD 4K)
Max Resolution Supported 3840x2160 pixels (UHD 4K) at 30Hz, 2560x1600 pixels @ 60Hz 2048x1536 pixels	at 30Hz, 2560x1600 pixels (@) 60Hz
PC PORT CONNECTORS	
Computer/Keyboard Mouse Wire USB Type A	
Computer Video Ports DVI-D VGA	DisplayPort
Computer Wire Length Channel 1 - 6 ft (1.8 m), Channel 2 - 6 ft (1.8 m)	
Computer Audio Jack 1/8" (3.5mm) male	
PHYSICAL	
Dimensions 4.3 (W) x 3 (D) x 1 (H) inch / 109.2 (W) x 76.2 (D) x (25.	4) mm
Weight 1.6 lbs / 0.73 Kg	
POWER	
Power Requirements 12V, 1A DC	
AC Input 100–240VAC	
Power Type External	
ENVIRONMENTAL	
Operating Temperature 32° to 104° F (0° to 40° C)	
Storage Temperature -4° to 140° F (-20° to 60° C)	
Humidity 0-80% RH, non-condensing	
CERTIFICATION	
Security Accreditation NIAP certified to latest Protection Profile PSS Ver 3.0, w 2.1.	hich exceeds EAL4 and PP PSS Ver.
Regulatory Compliance FCC class B, CE and ICES	
GENERAL INFORMATION	
OS Windows, Linux, Mac OS	
Made In Designed in California. Assembled in US with US and F	oreign components.
Product Life-Cycle 5 years	
Warranty 3 years	