



Large Rubber Base
For large-diameter
cup holder



Small Rubber Base
For smaller-diameter
cup holders



Small Rubber Base
with Adapter Cup
For VW Jetta and Golf
expanding cup holders

3 Options:

Belkin Corporation Limited Lifetime Product Warranty

Belkin Corporation warrants this product against defects in materials and workmanship for its lifetime. If a defect is discovered, Belkin will, at its option, repair or replace the product at no charge provided it is returned during the warranty period, with transportation charges prepaid, to the authorized Belkin dealer from whom you purchased the product. Proof of purchase may be required. This warranty does not apply if the product has been damaged by accident, abuse, misuse, or misapplication; if the product has been modified without the written permission of Belkin; or if any Belkin serial number has been removed or defaced.

THE WARRANTY AND REMEDIES SET FORTH ABOVE ARE EXCLUSIVE IN LIEU OF ALL OTHERS, WHETHER ORAL OR WRITTEN, EXPRESSED OR IMPLIED. BELKIN SPECIFICALLY DISCLAIMS ANY AND ALL IMPLIED WARRANTIES, INCLUDING, WITHOUT LIMITATION, WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

No Belkin dealer, agent, or employee is authorized to make any modification, extension, or addition to this warranty.

BELKIN IS NOT RESPONSIBLE FOR SPECIAL, INCIDENTAL, OR CONSEQUENTIAL DAMAGES RESULTING FROM ANY BREACH OF WARRANTY, OR ANY OTHER LEGAL THEORY, INCLUDING BUT NOT LIMITED TO, LOST PROFITS, DOWNTIME, GOODWILL, DAMAGE TO OR REPROGRAMMING OR REPRODUCING, ANY PROGRAM OR DATA STORED IN OR USED WITH BELKIN PRODUCTS.

Some states do not allow the exclusion or limitation of incidental or consequential damages or exclusion of implied warranties, so the above limitations or exclusions may not apply to you. This warranty gives you specific legal rights, and you may also have other rights that vary from state to state.



belkin.com

Belkin Corporation
501 West Walnut Street
Compton • CA • 90220 • USA
Tel: 310.898.1100
Fax: 310.898.1111

Belkin Components, Ltd.
Express Business Park • Sipton Way
Rushden • NN10 6GL • United Kingdom
Tel: +44 (0) 1933 35 2000
Fax: +44 (0) 1933 31 2000

Belkin Components B.V.
Starpac Building • Boeing Avenue 333
1119 PH Schiphol-Rijk • The Netherlands
Tel: +31 (0) 20 654 7300
Fax: +31 (0) 20 654 7349

Belkin, Ltd.
7 Bowen Crescent • West Gosford
NSW 2250 • Australia
Tel: +61 (0) 2 4372 8600
Fax: +61 (0) 2 4372 8603

Tech Support
US: 310.898.1100 ext. 2263
800.223.5546 ext. 2263
Europe: 00 800 223 55 460
Australia: 1800 666 040

© 2003 Belkin Corporation. All rights reserved. All trade names are registered trademarks of respective manufacturers listed. iPod is a trademark of Apple Computer, Inc.

P74388-A




TuneDok for iPod™

Take your iPod experience on the road



User Guide
F8E467

How to Set Up the TuneDok



For VW Jetta and Golf automobiles:

1. Insert the TuneDok's flexible cup into the small, rigid cup.
2. Push the three snaps through the corresponding holes in the bottom of the flexible cup. Make sure the two are firmly connected.
3. Insert the TuneDok cups into your car's cup holder. Ensure that the arm of the cup holder rests on top of the smaller cup's rim (Fig. 1). The smaller cup keeps your TuneDok firmly in place.



Fig. 2

To adjust the position of the iPod cradle:

1. Hold the TuneDok's flexible cup in one hand, and the iPod cradle in the other.
2. Twist the cradle clockwise to lower it, or counterclockwise to raise it (Fig. 2). Do not raise the cradle above the red line that's printed on the TuneDok's stem, as it will make the TuneDok unstable.
3. Place the TuneDok into your car's cup holder.
4. Turn the iPod cradle toward you and make sure that its position allows you to see and reach your iPod comfortably; adjust if necessary.




Fig. 3

To attach the cable of the Belkin Auto Kit:

1. Turn the TuneDok upside down.
2. On the underside, toward the front of the iPod cradle, you'll find a cable snap.
3. Thread the Auto Kit cable through here so it stays in place when you take your iPod out of the TuneDok (Fig. 3).




Fig. 4

To insert the iPod into the TuneDok:

1. Make sure the suction cup is clear of dust or dirt. If necessary, wipe it with a damp cloth.
2. Take off anything that may be connected to the dock connector.
3. Lay the dock connector end of the iPod into the bottom of the iPod cradle and gently push the iPod onto the suction cup.
4. Insert the Auto Kit connector into the dock connector of the iPod through the iPod cradle's bottom opening (Fig. 4).

For safety, always make sure that the TuneDok is securely resting inside your car's cup holder.




Fig. 5

To use TuneDok as a desk stand:

1. Hold the cradle firmly in one hand, and the rubber base in the other. Completely unscrew the Holder from the rubber cup.
2. Flip the base upside down.
3. Insert the screw into the opening on the bottom of the base, and twist clockwise. Make sure to turn the screw until the red marker is fully inserted into the base.
4. Adjust the height and angle to your liking.