




Protect secure computers with a NIAP-certified USB KVM switch

Designed specifically for secure military and government installations, the OmniView Secure KVM Switch lets you control multiple USB computers from a single USB console. This product ensures the integrity of your data by safely switching among computers running on different security levels. The OmniView Secure KVM Switch is NIAP Common Criteria validated to EAL 4.*

Available in 2-, 4-, and 8-port models, the Switch features a dedicated processor per computer port. This keeps each computer separate and secure at all times, and prevents data transfer among them. The device has no memory buffer or data-storage capability, making it impossible for your keystrokes and other data to unintentionally transfer as you switch between computers.

Security Features

Features	Benefits
Dedicated processor per computer port	Keeps computers running on different security levels separated; protects secure data and prevents data transfer among computers
No memory buffer	Prevents unintentional transfer of keystrokes or other data when switching between computers
No hot keys or on-screen display	Prevents data from being stored on KVM Switch
Non-reprogrammable firmware	Prevents tampering with KVM logic
Circuits soldered directly to circuit board	Prevents tampering with components
Tamper-evident tape on enclosure	Indicates that KVM Switch has been compromised; assures security when intact



Other Features

- **Rugged, metal enclosure** – provides stability and allows Switch to be placed beneath monitor or other desk item
- **Dedicated port selector per computer** – allows users to switch easily from one computer to the next
- **LED indicators** – provide easy identification of which computer is being accessed
- **Compact design** – allows for desktop or 1U rack-mountable installation**
- **USB support** – provides support for USB-compatible computers, keyboards, and mice
- **High video resolution** – supports video resolutions of up to 1920x1440@75Hz
- **3-Year Warranty and free technical support**

The OmniView Secure KVM Switch lets you safely control up to eight USB computers running on different security levels from a single USB console (4-port model shown).

*This product is certified by the National Information Assurance Partnership (NIAP). It is validated in accordance with the provisions of the NIAP Common Criteria Evaluation and Validation Scheme to EAL 4 (Evaluation Assurance Level 4).

**Requires optional Rack-Mount Kit (Belkin part number F1D005)

Recommended Belkin Accessories



Belkin All-In-One USB KVM Cable Kit

Offers the highest quality possible to ensure optimal data and video transmission. One Cable Kit is required per connected computer. Available in 6-, 10-, and 15-foot lengths. (F3X1962bXX)

(XX denotes cable length)



Rack-Mount Kit

Mounts your OmniView Secure KVM Switch to any 19-inch server rack. (F1D005)



Single-Rail LCD Rack Consoles

The Rack Console allows you to conveniently control racked servers from a single, secure, compact console. Available in 15" or 17".

(F1DC100S – 15")
(F1DC101S – 17")



Dual-Rail LCD Rack Consoles

The Rack Console allows you to conveniently control racked servers from a single, secure, compact console. Independently sliding rails allow the high-grade LCD to remain displayed, even with the keyboard stored.

(F1DC101P – 15")
(F1DC101R – 17")

Package Contents


OmniView Secure KVM Switch
5V DC, 2.6A Power Adapter
User Manual
Quick Installation Guide

Specifications

Model No.	F1DN102U	F1DN104U	F1DN108U
Enclosure	Metal with plastic faceplate	Metal with plastic faceplate	Metal with plastic faceplate
Operating Temperature	32° to 104° F (0 to 40° C)	32° to 104° F (0 to 40° C)	32° to 104° F (0 to 40° C)
Storage Temperature	-4° to 140° F (-20 to 60° C)	-4° to 140° F (-20 to 60° C)	-4° to 140° F (-20 to 60° C)
Power	5V DC, 2.6A power adapter	5V DC, 2.6A power adapter	5V DC, 2.6A power adapter
No. of Users Supported	1	1	1
No. of Computers Supported	2	4	8
Monitors Supported	CRT and LCD (with VGA support)	CRT and LCD (with VGA support)	CRT and LCD (with VGA support)
Keyboards/Mice Supported	USB	USB	USB
Resolution Support	Up to 1920x1440 @ 75Hz	Up to 1920x1440 @ 75Hz	Up to 1920x1440 @ 75Hz
CPU Keyboard/Mouse Ports	USB Type B	USB Type B	USB Type B
CPU Monitor Ports	HDDDB15 male (VGA)	HDDDB15 male (VGA)	HDDDB15 male (VGA)
Direct Port Selectors	2	4	8
LED Indicators	2	4	8
Dimensions	11 (W) x 1.75 (H) x 6 (L) in. (279 x 45 x 150mm)	11 (W) x 1.75 (H) x 6 (L) in. (279 x 45 x 150mm)	17 (W) x 1.75 (H) x 7.5 (L) in. (432 x 45 x 191mm)
Weight	2.5 lbs. (1.1kg.)	2.5 lbs. (1.1kg.)	4.25 lbs. (1.9kg.)
Warranty	3 years	3 years	3 years

Systems Supported

Windows® 2000, XP, Server 2003, Vista™
Mac OS® X v10.3 and above
Red Hat® Linux Desktop®, Red Hat Enterprise Linux WS



Part Number

Description

MSRP

F1DN102U.....	OmniView Secure 2-Port KVM Switch.....	\$299
F1DN104U.....	OmniView Secure 4-Port KVM Switch.....	\$399
F1DN108U.....	OmniView Secure 8-Port KVM Switch.....	\$999



Made in the USA of imported parts



Common Criteria

This product is TAA Trade Compliant.